



5 cable dSCR system

Cascadable single cable multiswitches

Cascadable single cable multiswitch for the distribution of SAT IF and DTT signals over one cable to up to 32 receivers per pair outputs.

- wideband / quattro LNB IF range, switchable
- control according legacy/EN50494/EN50607
- dSCR/Legacy mode automatic selection
- configurable with programmer PC102W
- dedicated control/configuration port
- DC input for external power supply
- current pass to H and V trunk lines, independent switching
- powering from H/V trunk lines
- powering status LED indication
- robust die-cast housing
- connectors:
 - RF inputs/outputs - type F
 - 2xDC inputs - type F

SRM564

active DTT path with AGC, six dSCR outputs

SRM584

active DTT path with AGC, eight dSCR outputs

SRM564T

passive DTT path, six dSCR outputs

SRM584T

passive DTT path, eight dSCR outputs



**SRM564
SRM564T**



**SRM584
SRM584T**

Technical specifications

T Y P E	SRM564	SRM584	SRM564T	SRM584T
Ordering number	03709	03710	03711	03712
Frequency range	SAT IF DTT	290-2350 MHz 47-862 MHz	5-862 MHz	
Number of trunk inputs & outputs	SAT IF DTT		4	1
Number of tap outputs	6 (3 pair)	8 (4 pairs)	6 (3 pair)	8 (4 pairs)
Trunk output loss	SAT IF DTT		< 4.0 dB < 4.0 dB	
Return loss / impedance			> 10 dB / 75 Ω	
Input level per channel	SAT IF DTT	55-85 dBμV (8 DTT channels) < 8 dB	65-105 dBμV	-
Terr. TV noise figure				-
Tap output with combined DTT	user bands (dSCR mode) user band bandwidth (dSCR mode) output level, AGC controlled (dSCR mode) output level, typical (legacy mode) DTT output level, AGC controlled DTT loss		32 max. per pair outputs, configurable 20-60 MHz, adjustable 84 dBμV, adjustable 78 dBμV 82 dBμV max. (8 DTT channels), adjustable -	
Decoupling	SAT IF inputs/SAT IF inputs SAT IF inputs/Tap outputs SAT IF / DTT		> 30 dB > 30 dB > 25 dB	18 dB
DC pass through trunk lines	SAT IF DTT		3.2 A max., 1.6 A max. through one line 200 mA max.	
Current consumption	from DC inputs*, H/V trunk lines from STB	20 V 740 mA max. 20 V 970 mA max. 18 V 20 mA max.	20 V 700 mA max.	20 V 930 mA max.
Current pass from DC inputs to each H/V trunk line, switchable	20 V 1.26 A max.	20 V 1.03 A max.	20 V 1.3 A max.	20 V 1.07 A max.
Operating temperature range			-20° ÷ + 50° C	
Dimensions/Weight (packed)			226x135x30 mm/0.8 kg	

* without external DC feeding