



5 cable system

Radial multiswitches

- for star distribution system of 4 SAT IF polarities and terrestrial TV signal up to 8 users
- passive terrestrial TV path
- built-in power supply for remote DC feeding
- possibility to feed preamplifier through terrestrial TV input
- die-cast housing

MRS504
5x4 multiswitch

MRS508
5x8 multiswitch



Technical specifications		MRS504	MRS508
T Y P E			
Ordering number		02759	02760
Number of outputs		4	8
Frequency range	SAT IF	950-2400 MHz	
	Terr. TV	5-862 MHz	
Gain (fixed slope pre-correction)	SAT IF	outputs 1-2 outputs 3-4 outputs 5-8	-6 ÷ 0 dB
		-7 ÷ -2 dB	-6 ÷ 0 dB
		-	-7 ÷ -2 dB
Attenuation	Terr. TV	outputs 1-4 outputs 5-8	12 dB 15 dB 15 dB
		-	
Output level for SAT IF (IMD3=35 dB)*		93 dB μ V	
SAT inputs decoupling		≥ 25 dB	
Outputs decoupling	SAT IF	≥ 25 dB	
	Terr. TV	≥ 25 dB	
Rejection		SAT/Terr. TV	≥ 40 dB
Supply voltage through RF inputs		H,Lo, H,Hi, V,Lo and V,Hi - 13 V; Terr. TV - 12 V	
DC supply current	+13V & +12V	≤ 0.27 A	
	through RF inputs	≤ 100 mA	
Current consumption from receiver		≤ 40 mA	
Control signals		14/18 V, 0/22 kHz	
Power consumption***		230 V~ 50/60 Hz 2 W	
Operating temperature range		-20° ÷ + 50° C	
Dimensions/Weight (packed)		200x137x52 mm/0.84 kg	

* 2 equal carriers

** without external DC load; with maximal external DC load 7 W